

Amend SB 745 as follows:

(1) On page 1, line 10, immediately prior to the period, insert "or the Grand Lakes Municipality Utility District, as appropriate. A reference to one district in this Act shall be a reference to both districts unless otherwise expressly provided in this Act."

(2) On page 1, strike lines 13 and 14 and substitute: "No. 4, and a municipal utility district, to be known as the Grand Lakes Municipal Utility District are created in Montgomery County, subject approval at separate confirmation elections under Section 9 of this Act."

(3) On page 2, strike lines 2 and 3 and insert the following: "SECTION 4. BOUNDARIES. (a) For the Grand Lakes Municipal Utility District: A tract or parcel of land containing 1413.23 acres, more or less, BEING 1413.23 total acres of land consisting of "Tract One" and "Tract Two". Tract One being of all of "Common Reserve", Grand Lake Estates Section Two recorded in Cabinet "N", Sheet 79, Real Property Records, Montgomery County, Texas. Said Tract One containing 28.39 acres of land, more or less. Tract Two being a 1384.84 acre tract of land, situated in the Archibald Hodge Survey, A-18, the John Sealy Survey, A-758, the Matthew Cartwright Survey A-135, and the Charles Dugat Survey, A-171, Montgomery County, Texas, being out of a 559.7036 acre tract recorded under Clerk's File No. 99091880, and a 1056.195 acre tract recorded under Clerk's File No. 99056276, Real Property Records, Montgomery County, Texas, Said Tract Two being more particularly described in the metes and bounds as follows: BEING a 1384.84 acre tract of land situated in the Archibald Hodge Survey, A-18, the John Sealy Survey, A-758, the Matthew Cartwright Survey A-135, and the Charles Dugat Survey, A-171, Montgomery County, Texas. Said tract being out of a 559.7036 acre tract recorded under Clerk's File No. 99091880, and a 1056.195 acre tract recorded under Clerk's File No. 99056276, Real Property Records, Montgomery County, Texas. Said 1384.84 acre tract being more particularly described as follows: BEGINNING at a 5/8" iron rod found for at the Northwest corner of Grand Lake Estates, Section Nine recorded in Cabinet "S", Sheet 193 & 194, Real Property Records, Montgomery County, Texas. Said rod being the most

easterly Northeast corner of the herein described tract; THENCE S 07 deg. 01' 08" W, a distance of 115.83 feet to a 5/8" iron rod set for corner; THENCE S 11 deg. 19' 39" E, a distance of 362.02 feet to a 5/8" iron rod set for corner; THENCE S 01 deg. 17' 33" E, a distance of 530.31 feet to a 5/8" iron rod set for corner; THENCE SOUTH, a distance of 147.44 feet to a 5/8" iron rod set for corner; THENCE S 01 deg. 14' 25" W, a distance of 407.79 feet to a 5/8" iron rod set for corner; THENCE S 22 deg. 37' 38" E, a distance of 294.95 feet to a 5/8" iron rod set for corner; THENCE S 58 deg. 40' 50" E, a distance of 243.47 feet to a 5/8" iron rod set for corner; THENCE S 82 deg. 46' 20" E, a distance of 626.07 feet to a 5/8" iron rod set for corner; THENCE S 39 deg. 41' 15" E, a distance of 532.87 feet to a 5/8" iron rod set for corner; THENCE S 32 deg. 40' 13" E, a distance of 218.61 feet to a 5/8" iron rod set for corner; THENCE S 10 deg. 26' 28" W, a distance of 185.29 feet to a 5/8" iron rod set for corner; THENCE S 41 deg. 59' 51" W, a distance of 123.32 feet to a 5/8" iron rod set for corner; THENCE SOUTH, a distance of 200.32 feet to a 5/8" iron rod set for corner; THENCE S 40 deg. 58' 55" E, a distance of 128.48 feet to a 5/8" iron rod set for corner; THENCE S 86 deg. 25' 57" W, a distance of 2446.48 feet to a 1/2" pine knot w/ tack found for corner; THENCE N 02 deg. 34' 42" W, a distance of 1563.07 feet to a fence post found for corner; THENCE S 86 deg. 54' 09" W a distance of 4735.48 feet to a fence post found for corner; THENCE S 02 deg. 25' 04" E, a distance of 1439.10 feet to a 1/2" iron rod found for corner; THENCE S 86 deg. 48' 56" W, a distance of 3747.25 feet to a fence post found for corner; THENCE N 04 deg. 09' 18" W, a distance of 1466.81 feet to a boiler pipe found for corner; THENCE S 87 deg. 18' 57" W, a distance of 1617.56 feet to a 1/2" iron rod found for corner; THENCE S 87 deg. 35' 34" W, a distance of 1612.68 feet to a 1/2" iron rod found for corner; THENCE S 02 deg. 35' 43" E, a distance of 4193.71 feet to a 5/8" iron rod found for corner; THENCE S 86 deg. 47' 39" W, a distance of 481.10 feet to a 5/8" iron rod found for corner; THENCE N 03 deg. 12' 21" W, a distance of 774.33 feet to a 5/8" iron rod found for corner; THENCE S 86 deg. 47' 39" W, a distance of 4894.23 feet to a 5/8" iron rod found for corner; THENCE N 03 deg. 59' 21" W, a distance of 1918.43 feet to a 4" iron rod found for corner; THENCE N 86 deg. 53' 08" E, a

distance of 1411.97 feet to a 4" iron rod found for corner; THENCE N 03 deg. 09' 10" W, a distance of 1483.04 feet to a 4" iron rod found for corner; THENCE N 86 deg. 49' 54" E, a distance of 2131.87 feet to fence post found for corner; THENCE N 00 deg. 38' 33" W, a distance of 1909.91 feet to a 5/8" iron rod found for corner; THENCE N 01 deg. 08' 05" W, a distance of 1026.24 feet to a 5/8" iron rod found for corner; THENCE N 00 deg. 15' 16" W, a distance of 112.23 feet to a 5/8" iron rod found for corner; THENCE S 89 deg. 36' 19" E, leaving said curve, a distance of 402.29 to a 5/8" iron rod found for corner; THENCE N 00 deg. 45' 35" W, a distance of 22.99 feet to a 5/8" iron rod set for corner; THENCE following a curve to the left having a radius of 168.97 feet, an arc length of 201.55 feet, a chord bearing of N 33 deg. 24' 39" E, a chord distance of 189.81 feet, and a central angle of 68 deg. 20' 28" to a 5/8" iron rod set for corner; THENCE S 45 deg. 54' 09" E, a distance of 395.72 feet to a 5/8" iron rod set for corner; THENCE S 80 deg. 28' 19" E, a distance of 165.13 feet to a 5/8" iron rod set for corner; THENCE N 64 deg. 02' 23" E, a distance of 298.49 feet to a 5/8" iron rod set for corner; THENCE S 34 deg. 32' 03" E, a distance of 440.01 feet to a 5/8" iron rod set for corner; THENCE S 13 deg. 36' 05" W, a distance of 19.22 feet to a 5/8" iron rod set for corner; THENCE S 80 deg. 00' 00" E, a distance of 255.64 feet to a 5/8" iron rod set for corner; THENCE N 10 deg. 00' 00" E, a distance of 75.46 feet to a 5/8" iron rod set for corner; THENCE S 80 deg. 00' 00" E, a distance of 527.93 feet to a 5/8" iron rod set for corner; THENCE N 13 deg. 49' 27" E, a distance of 371.174 feet to a 5/8" iron rod set for corner; THENCE N 68 deg. 49' 52" W, a distance of 481.42 feet to a 5/8" iron rod set for corner; THENCE N 02 deg. 36' 41" W, a distance of 463.18 feet to a 5/8" iron rod set for corner; THENCE N 39 deg. 43' 35" E, a distance of 66.51 feet to a 5/8" iron rod set for corner; THENCE S 60 deg. 31' 41" E, a distance of 513.34 feet to a 5/8" iron rod set for corner; THENCE S 76 deg. 32' 37" E, a distance of 240.79 feet to a 5/8" iron rod set for corner; THENCE N 42 deg. 56' 06" E, a distance of 514.37 feet to a 5/8" iron rod set for corner; THENCE N 13 deg. 05' 08" W, a distance of 197.92 feet to a 5/8" iron rod set for corner; THENCE N 83 deg. 11' 23" E, a distance of 248.21 feet to a 5/8" iron rod set for corner; THENCE S 13 deg.

05' 08" E, a distance of 16.86 feet to a 5/8" iron rod set for corner; THENCE N 83 deg. 11' 23" E, a distance of 241.60 feet to a 5/8" iron rod set for corner; THENCE N 06 deg. 17' 39" E, a distance of 63.17 feet to a 5/8" iron rod set for corner; THENCE N 34 deg. 26' 11" E, a distance of 66.65 feet to a 5/8" iron rod set for corner; THENCE N 01 deg. 50' 54" W, a distance of 38.31 feet to a 5/8" iron rod set for corner; THENCE N 05 deg. 02' 40" E, a distance of 135.34 feet to a 5/8" iron rod set for corner; THENCE N 83 deg. 11' 23" E, a distance of 46.95 feet to a 5/8" iron rod set for corner; THENCE S 22 deg. 45' 31" E, a distance of 123.44 feet to a 5/8" iron rod set for corner; THENCE S 46 deg. 07' 36" E, a distance of 85.93 feet to a 5/8" iron rod set for corner; THENCE S 27 deg. 13' 26" E, a distance of 199.65 feet to a 5/8" iron rod set for corner; THENCE S 00 deg. 28' 34" W, a distance of 117.40 feet to a 5/8" iron rod set for corner; THENCE S 26 deg. 34' 06" W, a distance of 153.52 feet to a 5/8" iron rod set for corner; THENCE S 09 deg. 43' 52" E, a distance of 87.19 feet to a 5/8" iron rod set for corner; THENCE S 48 deg. 01' 24" E, a distance of 99.11 feet to a 5/8" iron rod set for corner; THENCE N 48 deg. 26' 34" E, a distance of 58.73 feet to a 5/8" iron rod set for corner; THENCE S 72 deg. 47' 01" E, a distance of 52.55 feet to a 5/8" iron rod set for corner; THENCE S 05 deg. 40' 46" W, a distance of 109.61 feet to a 5/8" iron rod set for corner; THENCE N 88 deg. 51' 58" E, a distance of 136.71 feet to a 5/8" iron rod set for corner; THENCE N 23 deg. 45' 12" E, a distance of 373.71 feet to a 5/8" iron rod set for corner; THENCE with a curve to the left, having a radius of 359.90 feet, an arc length of 199.34 feet, a chord bearing of S 71 deg. 31' 28" E, a chord distance of 196.80, and a central angle of 31 deg. 44' 04", to a 5/8" iron rod found for corner; THENCE N 88 deg. 51' 58" E, a distance of 703.56 feet to a 5/8" iron rod found for corner; THENCE S 03 deg. 55' 29" E, a distance of 551.39 feet to a 5/8" iron rod set for corner; THENCE S 04 deg. 03' 59" E, a distance of 191.76 feet to a 5/8" iron rod set for corner; THENCE S 83 deg. 33' 48" E, a distance of 279.69 feet to a 5/8" iron rod set for corner; THENCE S 23 deg. 30' 47" E, a distance of 390.65 feet to a 5/8" iron rod set for corner; THENCE S 66 deg. 33' 01" E, a distance of 359.88 feet to a 5/8" iron rod set for corner; THENCE N 81 deg. 42' 44" E, a distance of 742.77 feet to

a 5/8" iron rod set for corner; THENCE S 34 deg. 40' 50" E, a distance of 327.59 feet to a 5/8" iron rod set for corner; THENCE N 88 deg. 56' 36" E, a distance of 7034.57 feet to a 5/8" iron rod set for corner; THENCE N 86 deg. 29' 16" E, a distance of 939.67 feet to a 5/8" iron rod set for corner; THENCE N 86 deg. 28' 07" E, a distance of 139.29 feet the POINT OF BEGINNING, containing 1384.84 acres of land, more or less.

(b) For the boundaries of the East Montgomery County Utility District No. 4: "

(4) Amend the caption to conform to the body of the bill.